



Pevalit P XS

Quick Flexible
adhesive



APPLICATION

- Modified adhesive for quick solidification after use.
- Is used over layers of not properly dried concrete or plaster.
- Adhesive of tiles in the system tile on tile, or flooring with heating system, or swimming pools.
- Used for adhesive of tiles from granite and natural marble, porcelain tiles, mosaic stone, glass, ceramics, etc.
- Has high durability against high temperatures, frost and moisture.
- Certified in C2FT class, by norm EN 12004.
- Usage time after mixing 15 minutes.

Toothed Shovel Dimensions	Consumption	Surface Covered with 25kg PEVALIT-P XS
6x6x6 mm	approx. 2.1 kg/m ²	approx. 11.6 m ²
8x8x8 mm	approx. 2.8 kg/m ²	approx. 8.8 m ²
10x10x10 mm	approx. 3.6 kg/m ²	approx. 7 m ²

- Working time in container:** Up to 15 minutes after mixing.
- Working time:** Up to 10 minutes.
- Work temperatures:** +15°C - +30°C
- Resistant to temperatures:** -35°C - +100°C
- Norm:** C2FT, based on EN 12004.
- Walking on tiles:** After 3-6 hours. Measurements are based on temp. around 22°C.
- Walking on tiles with weight:** After 6 hours.
- On layers of plaster:** PEVALIT-Tiefgrund LF is used.
- Mixing with water:** approximately 4 min., with around 24 % water / 25kg.
- Packaging:** 25 kg.
- Material color:** White.
- Best before:** In the original packaging 12 months, in a warehouse without moisture.