



APPLICATION

- One-component polyurethane foam.
- For filling gaps between EPS thermal insulation panels.
- Installation of doors, windows, fittings, blinds, etc.
- Substrates where PEVALIT-PE-1K pistolenschaum is used it should be hard, clean, fat-free and dry.

Pevalit

PE-1K

One component polyurethane foam

CONSUMPTION

Grout width and thickness	Surface covered with 300 ml PEVALIT - PE 1K
5x5 mm	approx. 12.0 meters length
10x10 mm	approx. 3.0 meters length

TECHNICAL PARAMETERS

- Temperatures of use:** from +5°C - +25°C.
- Resistant to temperatures:** -40°C - +110°C.
- Drying(23°C/50%):** approx. 10 min.
- Drying(23°C/50%):** approx. 60 min for 3 cm thickness.
- Thermal permeability:** 0.03 W/mK
- Pressure resistance (10%(DIN 53421):** 3.3 N/cm2
- Purpose and Water absorption (DIN53429):** 70gr/(m2h24)
- Material loss:** max. 3%.
- Cleaning:** with PU-Reiniger
- Packaging:** in tubes 750ml; (12 tubes/packet).
- Best before:** In the original packaging 12 months, in a warehouse without moisture, jashtë ndikimit të frost.

