

PEVALIT P3 S1



High Flexibility Adhesive

APPLICATION

- Used for adhesive of tiles from granite and natural marble, porcelain tiles, mosaic stone, glass, ceramics, etc.
- Adhesive of tiles in the system tile on tile, or flooring with a heating system.
- Adhesive of tiles on swimming pools.
- Before adhesive on layers of wood, PVC or metal binding liquid must be used.
- Good features for usage on nonporous and smooth layers.
- Has high durability against high temperatures, frost and moisture.
- Certified in C2TE-S1 class.

TECHNICAL PARAMETERS

Toothed Shovel Dimensions	Spending	Surface covered with 25kg PEVALIT - P3 S1
6x6x6 mm	approx. 2.1kg/m ²	approx. 11.6m ²
8x8x8 mm	approx. 2.8kg/m ²	approx. 8.8m ²
10x10x10 mm	approx. 3.6kg/m ²	approx. 7m ²

- Working time in container:** Up to 4 hours after mixing.
 - Working time:** Up to 30 minutes.
 - Work temperatures:** +5°C - +30°C
 - Resistant to temperatures:** -30°C - +100°C
 - Norm:** C2FE - S1, based on EN 12004.
 - Walking on tiles:** After 12-16 hours.
- Measurements are based on temp. around 22°C.
- Walking on tiles with weight:** After 4 days.
 - On layers of plaster:** PEVALIT-Tiefgrund LF is used.
 - Mixing with water:** approximately 4 min., with around 24 % water / 25kg.
 - Packaging:** 25 kg.
 - Material color:** Grey.
 - Best before:** In the original packaging 12 months, in a warehouse without moisture.