

# PEVALIT P100



## Tile Adhesive

### APPLICATION

- Used for ceramic tile adhesive in indoor environments.
- On walls or floor.
- Gas Beton Block adhesive and leveling.
- Filling thickness up to 2 cm.

### TECHNICAL PARAMETERS

Toothed Shovel Dimensions	Spending	Surface covered with 25kg PEVALIT - P100
4x4x4 mm	approx. 2 kg/m <sup>2</sup>	approx. 12 m <sup>2</sup>
6x6x6 mm	approx. 3 kg/m <sup>2</sup>	approx. 8 m <sup>2</sup>
8x8x8 mm	approx. 4 kg/m <sup>2</sup>	approx. 6 m <sup>2</sup>

- Working time in container:** Up to 6 hours after mixing.
- Working time:** Up to 10 minutes.
- Work temperatures:** +5°C - +30°C
- Resistant to temperatures:** -10°C - +50°C
- Norm:** C1, based on EN 12004.
- Walking on tiles:** After 24 hours.
- Walking on tiles with weight:** After 5 days.
- On layers of plaster:** PEVALIT-Tiefgrund LF is used.
- Mixing with water:** approximately 4 min., with around 24 % water / 25kg.
- Packaging:** 25 kg.
- Material color:** White.
- Best before:** In the original packaging 12 months, in a warehouse without moisture.