

PEVALIT P midiflex



Flexible Tile Adhesive

APPLICATION

- Used for porcelain tile adhesive, artificial granite, concrete tiles, stone, ceramics, etc.
- For surfaces of outdoor and indoor environments, for example terraces, balconies, facades, etc.
- Tile adhesive over layers of flooring with central heating system.
- Has good durability against high temperatures, frost and moisture.
- For use on walls and flooring.
- Certified in C2TE class, according to norm EN 12004

TECHNICAL PARAMETERS

Toothed Shovel Dimensions	Spending	Surface covered with 25kg PEVALIT - P midiflex
4x4x4 mm	approx. 1.5kg/m ²	approx. 16m ²
6x6x6 mm	approx. 2.3kg/m ²	approx. 11m ²
8x8x8 mm	approx. 3.1kg/m ²	approx. 8m ²
10x10x10 mm	approx. 3.9kg/m ²	approx. 6.4m ²

- Working time in container:** Up to 6 hours after mixing.
- Working time:** Up to 30 minutes.
- Work temperatures:** +5°C - +30°C
- Resistant to temperatures:** -20°C - +80°C
- Norm:** C2TE, based on EN 12004.
- Walking on tiles:** After 24 hours. Measurements are based on temp. around 22°C.
- Walking on tiles with weight:** After 4 days.
- On layers of plaster:** PEVALIT-Tiefgrund LF is used.
- Mixing with water:** approximately 4 min., with around 24 % water / 25kg.
- Packaging:** 25 kg.
- Material color:** White.
- Best before:** In the original packaging 12 months, in a warehouse without moisture.