

# PEVALIT P3



## High Flexibility Adhesive

### APPLICATION

- Used for tile adhesive on flooring layers with heating system.
- Adhesive of tiles of granite, marble, porcelain, mosaic stone, glass, ceramics, etc.
- Adhesive of tiles on swimming pools.
- Adhesive of tiles on cold rooms.
- For use on outdoor and indoor environments.
- For use on walls and flooring.
- Has good durability against high temperatures, frost and moisture.
- Certified in C2TE class, according to norm EN 12004.

### TECHNICAL PARAMETERS

Toothed Shovel Dimensions	Spending	Surface covered with 25kg PEVALIT - P3
6x6x6 mm	approx. 2.1kg/m <sup>2</sup>	approx. 11.6m <sup>2</sup>
8x8x8 mm	approx. 2.8kg/m <sup>2</sup>	approx. 8.8m <sup>2</sup>
10x10x10 mm	approx. 3.6kg/m <sup>2</sup>	approx. 7m <sup>2</sup>

- Working time in container:** Up to 6 hours after mixing.
- Working time:** Up to 30 minutes.
- Work temperatures:** +5°C - +30°C
- Resistant to temperatures:** -30°C - +95°C
- Norm:** C2TE, based on EN 12004.
- Walking on tiles:** After 24-48 hours. Measurements are based on temp. around 22 °C.
- Walking on tiles with weight:** After 4 days.
- On layers of plaster:** PEVALIT-Tiefgrund LF is used.
- Mixing with water:** approximately 4 min., with around 24 % water / 25kg.
- Packaging:** 25 kg.
- Material color:** Grey.
- Best before:** In the original packaging 12 months, in a warehouse without moisture.